


Seguidor de leva CR30-VBR-IKO - CR30-VBR-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr30-vbr-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



Stud dia. mm (inch)	Identification number		Shield type With cover With cylindrical outer ring	Screw type		Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	CR 30	VBR		With cylindrical outer ring	With cylindrical outer ring						
19.050 ($\frac{3}{4}$)	CR 30	VBR				418	47.625 ($1\frac{7}{8}$)	25.400 (1)	19.050 ($\frac{3}{4}$)	7-16	22.225 ($\frac{7}{8}$)
Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum spinning torque N-m	Basic dynamic load rating C	Basic static load rating C ₀	
B max	B ₂	B ₃	C ₁	g ₁	g ₂	H					r
25.8 1.06	44.450 ($1\frac{3}{4}$)	11.112 ($\frac{1}{2}$)	0.794 ($\frac{1}{8}$)	4.792 ($\frac{3}{8}$)	3.969 ($\frac{5}{16}$)	7.938 ($\frac{5}{8}$)	1.588 ($\frac{1}{8}$)	32.543 ($1\frac{1}{8}$)	100	35 300	55 600

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060464132
Diámetro interior	19.05 mm
Diámetro exterior	47.625 mm
Espesor	25.4 mm
Peso	418 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE