


Seguidor de leva CR36-VBUU-IKO - CR36-VBUU-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/seguidor-leva/cr36-vbuu-iko>

IKO
CAM FOLLOWERS
Inch Series Cam Followers **With Cage/With Screwdriver Slot**



CR36-VBUU

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
22.225 ($\frac{7}{8}$)				CR 36 VBUU	759	57.150 (2 $\frac{1}{2}$)	31.750 (1 $\frac{1}{2}$)	22.225 (7/8)	7-14	25.400 (1)	
Boundary dimensions mm (inch)						Mounting dimension f Min. mm (inch)	Maximum spinning torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
33.5 (1.32)	50.800 (2)	12.700 (1/2)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	4.762 ($\frac{3}{16}$)	11.112 (1 $\frac{1}{8}$)	1.588 ($\frac{1}{16}$)	37.305 (1 $\frac{3}{8}$)	162	45 700	80 600

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060464323
Diámetro interior	22.225 mm
Diámetro exterior	57.15 mm
Espesor	31.75 mm
Peso	759 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE