

Rodamiento de agujas BHTM916-JTEKT - BHTM916-KOYO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/bhtm916-koyo>

Drawn cup needle roller bearings



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F _w	D	C	b min.	C ₁₀	C ₉₀	Oil lub.		Caged type	
								With open ends	With closed end
9	16	16	13.3	7.95	7.90	32 000		BHTM916	

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	8.991	9.000	15.977	15.995	12	13

CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952469485
Diámetro interior	9 mm
Diámetro exterior	16 mm
Espesor	16 mm
Peso	12 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE