

## Rodamiento de agujas 15BTM2122-JTEKT - 15BTM2122-KOYO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/15btm2122-koyo>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
F <sub>w</sub>	D	C	b min.	C <sub>0</sub>	C <sub>0r</sub>	Oil lub.	Caged type	
							With open ends	With closed end
15	21	22	—	13.0	19.5	23 000	<b>15BTM2122</b>	

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	14.989	15.000	20.991 <sup>4)</sup>	21.012 <sup>4)</sup>	20	—

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952470177
Diámetro interior	15 mm
Diámetro exterior	21 mm
Espesor	22 mm
Peso	20 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE