


## Rodamiento rodillos NN3022K-JTEKT - NN3022K-KOYO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/rodillos/nn3022k-koyo>

Double-row cylindrical roller bearings **Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
d	D	B	r min.	F <sub>w</sub>	E <sub>a</sub>	C	C <sub>107</sub>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
110	170	45	2	—	155	221	361	3 500	4 200	—	NN3022K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	d <sub>a</sub>		D <sub>a</sub>		r <sub>a</sub>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		119	—	—	161	157	2	3.65	3.56

### CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
Nº Ean13	3663952473062
Diámetro interior	110 mm
Diámetro exterior	170 mm
Espesor	45 mm
Peso	3560 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE