

## Rodamiento de agujas NQ20-20-JTEKT - NQ20-20-KOYO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/agujas/nq20-20-koyo>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.	Grease lub.	Without inner ring	
20	—	28	20	14.4	23.0	23 000	—	NQ20/20	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring	—			
	$d_2$	$D_2$	$r_2$	0.038	—	—			
	max.	max.	max.	—	—	—			
	—	26	0.3	—					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	JTEKT
N° Ean13	3663952477435
Diámetro interior	20 mm
Diámetro exterior	28 mm
Espesor	20 mm
Peso	38 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE