


Rodamiento axial de agujas AZK8015010-IKO - AZK8015010-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/axial-agujas/azk8015010-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings



Shaft dia. mm	Identification number							
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
80	AZ 8015026	2 500	AZK 8015010	920	WS 80150	GS 80150	790	

Boundary dimensions mm										Standard mounting dimensions mm	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾	
d	D	T	d _c	D _c	D _w	B	r _s min ⁽¹⁾	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
80	150	26	80.05	149.5	10	8	1.5	99	139	139	100	180 000	792 000	2 500

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3616060466105
Diámetro interior	80 mm
Diámetro exterior	150 mm
Espesor	10 mm
Peso	920 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE