


Rodamiento axial de agujas AZK28044030-IKO - AZK28044030-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/axial-agujas/azk28044030-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
280	AZ 28044080	54 600	AZK 28044030	19 200	WS 280440	GS 280440	17 700

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
280	440	80	280.15	438	30	25	5	309	422	420	311	1 420 000	7 490 000	800

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952487991
Diámetro interior	280 mm
Diámetro exterior	440 mm
Espesor	30 mm
Peso	19200 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE