

# Rotulas SI

## DSIL5-T-K-DURBAL - SIL5-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/sil5-t-k-durbal>


### DSIL5-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE composite

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number	right hand thread	left hand thread	measurement (mm)						
DSIL 5 T/K			d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
			5	M 5	8	6,00	18	8,5	11

type	measurement (mm)			h	d <sub>1</sub>	load rating C <sub>10</sub> (N)	weight (kg)
	l <sub>1</sub> min	W					
DSI / DSIL 5 T/K	10	9	27	13	6,0	0,016	

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952489070
Diámetro interior	5 mm
Diámetro exterior	18 mm
Espesor	8 mm
Tipo	SI
Peso	16 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE