

# Rotulas SI

## SIL14-T-K-DURBAL - SIL14-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/sil14-t-k-durbal>


### SIL14-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



**Rod end body:**  
surface zinc plated

**Sliding combination:**  
steel / bronze-PTFE composite

**Inner ring:**  
bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:**  
brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:**  
maintenance free

order number	right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SIL 14 T/K			14	M 14	19	13,50	36	20,0	25

type	measurement (mm)			h	d1	load rating C1 (N)	weight (kg)
	l1 min	W					
SI / SIL 14 T/K	25	22	57	16	31,0	0,160	

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952489339
Diámetro interior	14 mm
Diámetro exterior	36 mm
Espesor	19 mm
Tipo	SI
Peso	160 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE