

Rotulas SI DSIL18-T-K-DURBAL - DSIL18-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/dsil18-t-k-durbal>

DSIL18-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	right hand thread	left hand thread	measurement [mm]					
DSIL 18 T/K	18	M 18 x 1,5	23	16,50	44	25,0	31	

type	measurement [mm]			load rating C ₀ [N]	weight [kg]
	l ₃ min	W	h		
DSI / DSIL 18 T/K	32	27	71	15	47,5

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952489506
Diámetro interior	18 mm
Diámetro exterior	44 mm
Espesor	23 mm
Tipo	SI
Peso	320 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE