

# Rotulas SI

## SIL22-T-K-DURBAL - SIL22-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/sil22-t-k-durbal>

### SIL22-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE composite

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number	right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SIL 22 T/K			22	M 22 x 1,5	28	20,00	54	30,0	38

type	measurement (mm)			h	d <sub>1</sub>	load rating C <sub>10</sub> (N)	weight (kg)
	l <sub>1</sub> min	W					
SI / SIL 22 T/K	37	32	84	15	68,0	0,540	

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952489575
Diámetro interior	22 mm
Diámetro exterior	54 mm
Espesor	28 mm
Tipo	SI
Peso	540 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE