

Rotulas SI SI28-T-K-DURBAL - SI28-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/si28-t-k-durbal>


SI28-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 28 TIK		28	M 27 x 2	35	24,00	66	37,0	46

type	measurement [mm]			d ₁	load rating C ₁₀ [N]	weight [kg]
	l ₁ min	W	h			
SI / SIL 28 TIK	51	41	103	15	107,0	0,820

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952489681
Diámetro interior	28 mm
Diámetro interior	1.102" inch
Diámetro exterior	66 mm
Diámetro exterior	2.598" inch
Espesor	35 mm
Espesor	1.378" inch
Tipo	SI
Peso	820 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE