

## Rotulas SI SIL50-T-K-DURBAL - SIL50-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/sil50-t-k-durbal>


### SIL50-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE composite

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
	SIL 50 T/K	50	M 48 x 2	60	45,00	117	65,0	75

type	measurement [mm]			d <sub>1</sub>	load rating C <sub>10</sub> [kN]	weight [kg]
	l <sub>3</sub> min	W	h			
SI / SIL 50 T/K	65	65	160	12		5,000

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952489889
Diámetro interior	50 mm
Diámetro exterior	117 mm
Espesor	60 mm
Tipo	SI
Peso	5000 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE