

Rotulas SA DSAL6-T-K-DURBAL - DSAL6-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/dsal6-t-k-durbal>


DSAL6-T-K



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
DSAL 6 T/K		6	M 6	9	6,75	20	
type	l ₁ min	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
DSA / DSAL 6 T/K	21	l ₁	l ₂	36	13	7,7	0,020

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952489940
Diámetro interior	6 mm
Diámetro exterior	20 mm
Espesor	9 mm
Tipo	SA
Peso	20 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE