

Rotulas SA SAL22-T-K-DURBAL - SAL22-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/sal22-t-k-durbal>

SAL22-T-K



male thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

Rod end body: surface zinc plated



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 22 T/K		22	M 22 x 1,5	28	20,00	54

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 22 T/K	48	27	84	15	68,0	0,480

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952490250
Diámetro interior	22 mm
Diámetro exterior	54 mm
Espesor	28 mm
Tipo	SA
Peso	480 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE