

Rotulas SA SA40-T-K-DURBAL - SA40-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/sa40-t-k-durbal>


SA40-T-K



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SA 40 T/K		40	M 42 x 2	49	33,00	91

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 40 T/K	90	46	150	17		2,300

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952490458
Diámetro interior	40 mm
Diámetro interior	1.575" inch
Diámetro exterior	91 mm
Diámetro exterior	3.583" inch
Espesor	49 mm
Espesor	1.929" inch
Tipo	SA
Peso	2300 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE