

Rotulas SI

DSSIL5-T-K-DURBAL - SSIL5-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/ssil5-t-k-durbal>

DSSIL5-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 5 T/K			d	G	B	C1	d1	d2	d3	d4
			5	M 5	8	6,00	18	8,5	11	

type	measurement [mm]				load rating C ₀ [kN]	weight [g]
	l ₁ min	W	h	α [°]		
DSSI / DSSIL 5 T/K	10	9	27	13	6,0	0,016

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952491080
Diámetro interior	5 mm
Diámetro exterior	18 mm
Espesor	8 mm
Tipo	SI
Peso	16 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE