

Rotulas SI

DSSIL6-T-K-DURBAL - DSSIL6-T-K-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/dssil6-t-k-durbal>

DSSIL6-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 6 T/K			d	G	B	C1	d1	d2	d3	d4
			6	M 6	9	6,75	20	10,0	13	

type	measurement [mm]				load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h	α		
DSSI / DSSIL 6 T/K	12	11	30	13	7,7	0,022

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952491097
Diámetro interior	6 mm
Diámetro exterior	20 mm
Espesor	9 mm
Tipo	SI
Peso	22 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE