

## Rotulas SI DSIL12-PK-DURBAL - DSIL12-PK-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/dsil12-pk-durbal>

### DSIL12-PK



**female thread; maintenance free, according to DIN ISO 12240-4, series K**

**Description:** DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.

**End end body:** surface case plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel hardened and ground

**Outer ring:** rod end body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free

| order number      | d  | G    | measurement (mm) |       |                |                |
|-------------------|----|------|------------------|-------|----------------|----------------|
| right hand thread | 12 | M 12 | B                | C     | d <sub>1</sub> | d <sub>2</sub> |
| <b>DSIL 12 PK</b> | 12 | M 12 | 16               | 12,00 | 33             | 17,5           |

| type             | l <sub>1</sub> min | measurement (mm) |    |       | load rating         | weight |
|------------------|--------------------|------------------|----|-------|---------------------|--------|
| DSI / DSIL 12 PK | 22                 | W                | h  | α [°] | C <sub>9</sub> (DN) | (kg)   |
|                  |                    | 19               | 50 | 13    | 24,00               | 0,100  |

## CARACTERÍSTICAS DEL PRODUCTO

|                   |                 |
|-------------------|-----------------|
| Marca             | DURBAL          |
| Nº Ean13          | 3663952491974   |
| Diámetro interior | 12 mm           |
| Diámetro exterior | 33 mm           |
| Espesor           | 16 mm           |
| Tipo              | SI              |
| Peso              | 100 g           |
| Hilo              | Rosca izquierda |
| Lubricación       | sin             |
| Envasado          | 1               |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE