

Rotulas SA DSA6-BK-DURBAL - DSA6-BK-DURBAL


<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/dsa6-bk-durbal>

DSA6-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated
Sliding combination:
steel / bronze-PTFE composite
Inner ring:
bearing steel hardened and ground
Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite
Lubrication:
maintenance free

| order number | measurement [mm] | | measurement [mm] | | |
|--------------|------------------|-----|------------------|----------------|----------------|
| | d | G | B | C ₁ | d ₂ |
| DSA 6 BK | 6 | M 6 | 9 | 6,7 | 21 |

| type | measurement [mm] | | α [°] | load rating C ₀ [kN] | weight [g] |
|-----------------|--------------------|----|-------|---------------------------------|------------|
| | l ₁ min | h | | | |
| DSA / DSAL 6 BK | 22 | 36 | 11 | 7,65 | 0,020 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | DURBAL |
| N° Ean13 | 3663952492391 |
| Diámetro interior | 6 mm |
| Diámetro interior | 0.236" inch |
| Diámetro exterior | 21 mm |
| Diámetro exterior | 0.827" inch |
| Espesor | 9 mm |
| Espesor | 0.354" inch |
| Tipo | SA |
| Peso | 20 g |
| Hilo | Rosca derecha |
| Lubricación | sin |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE