

Rotulas GE GAR45-UK-2RS-DURBAL - GAR45-UK-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/gar45-uk-2rs-durbal>

GAR45-UK-2RS



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement (mm)	
right hand thread	d	G
left hand thread	B	C1
GAR 45 UK-2RS	45	M 42 x 3
	32	27,0
		102

type	l, min	measurement [mm]	h	alpha [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 45 UK-2RS	94	52	163	7	240,0	2,600

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3616060467706
Diámetro interior	45 mm
Diámetro exterior	102 mm
Espesor	32 mm
Tipo	GE
Peso	2600 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE