

Rotulas GE

GAR50-UK-2RS-DURBAL - GAR50-UK-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/gar50-uk-2rs-durbal>


GAR50-UK-2RS



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)		measurement (mm)		measurement (mm)	
right hand thread	d	G	B	C ₁	d ₂	
GAR 50 UK-2RS	50	M 45 x 3	35	30,0	112	

type	l, min	measurement (mm)	h	a	load rating	weight
		l ₁ min		[°]	C ₀ (kN)	(kg)
GAR / GAL 50 UK-2RS	107	60	185	6	290,0	3,400

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3616060467737
Diámetro interior	50 mm
Diámetro exterior	112 mm
Espesor	35 mm
Tipo	GE
Peso	3400 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE