

# Rotulas GE

## GAL50-UK-2RS-DURBAL - GAL50-UK-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/ge/gal50-uk-2rs-durbal>


### GAL50-UK-2RS



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	d	G	B	C1	d2
GAL 50 UK-2RS	50	M 45 x 3	35	30,0	112

type	l1, min	l2, min	h	$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight (kg)
GAR / GAL 50 UK-2RS	107	60	185	6	290,0	3,400

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3616060467744
Diámetro interior	50 mm
Diámetro exterior	112 mm
Espesor	35 mm
Tipo	GE
Peso	3400 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1
Estándar	Ninguna norma

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE