

Rotulas SI

GIR12-UK-DURBAL - GIR12-UK-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/gir12-uk-durbal>

GIR12-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	d	G	B	measurement [mm]	C ₁	C ₂	d ₂	d ₄
GIR 12 UK	12	M12	10	8,0	34	17,5	22	

type	measurement [mm]	load rating	weight
	l_3 min h W	C ₀ (kN)	[kg]
GIR / GRL 12 UK	23 50 19	11	24,5 0,096

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952493695
Diámetro interior	12 mm
Diámetro exterior	34 mm
Espesor	10 mm
Tipo	SI
Peso	96 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE