

Rotulas SI

GIR15-UK-DURBAL - GIR15-UK-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/gir15-uk-durbal>

GIR15-UK



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free



order number	d	G	B	C ₁	d ₂	d ₃	d ₄
GIR 15 UK	15	M 14	12	10,0	40	21,0	26

type	measurement [mm]				load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W	α [°]		
GIR / GIR 15 UK	30	61	22	8	36,0	0,180

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952493725
Diámetro interior	15 mm
Diámetro exterior	40 mm
Espesor	12 mm
Tipo	SI
Peso	180 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE