

Rotulas SI GIL17-UK-DURBAL - GIL17-UK-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/gil17-uk-durbal>

GIL17-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number right hand thread	measurement [mm]						
	d	G	B	C ₁	d ₂	d ₄	W
GIL 17 UK	17	M 16	14	11,0	46	24,0	30
type	measurement [mm]			load rating C ₀ [kN]	weight [kg]		
	t ₃ min	h	W				
GIR / GIL 17 UK	34	67	27	45,0	0,220		

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952493763
Diámetro interior	17 mm
Diámetro interior	0.669" inch
Diámetro exterior	46 mm
Diámetro exterior	1.811" inch
Espesor	14 mm
Espesor	0.551" inch
Tipo	SI
Peso	220 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE