

Rotulas SI GIR25-UK-DURBAL - GIR25-UK-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/gir25-uk-durbal>

GIR25-UK



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]						
GIR 25 UK	d	G	B	C ₁	d ₂	d ₄	
	25	M 24 x 2	20	17,0	64	33,5	42
type	measurement [mm]			load rating	weight		
	t _{3 min}	h	W	C ₀ [kN]	[kg]		
GIR / GIR 25 UK	48	94	36	83,0		0,640	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952493978
Diámetro interior	25 mm
Diámetro interior	0.984" inch
Diámetro exterior	64 mm
Diámetro exterior	2.52" inch
Espesor	20 mm
Espesor	0.787" inch
Tipo	SI
Peso	640 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE