

Rotulas SI

GIR30-UK-2RS-DURBAL - GIR30-UK-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/gir30-uk-2rs-durbal>

GIR30-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]	
GIR 30 UK (-2RS)	d	G
	B	C ₁
	d ₂	d ₄
	h	W
	α	
	load rating	weight
	C ₀	[kg]
	[kN]	
GIR / GIL 30 UK	30	M 30 x 2
	22	19,0
	73	40,0
	50	
	56	110
	41	6
	110,0	0,930

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952494012
Diámetro interior	30 mm
Diámetro exterior	73 mm
Espesor	22 mm
Tipo	SI
Peso	930 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE