

# Rotulas SI

## GIR35-UK-2RS-DURBAL - GIR35-UK-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/gir35-uk-2rs-durbal>

### GIR35-UK-2RS



**female thread:** maintenance free, according to DIN ISO 12240-4; series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE fabric

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** steel body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** no lubrication necessary, maintenance free



order number	right hand thread	left hand thread	measurement [mm]						
			d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>	
GIR 35 UK-2RS			35	M 36 x 3	25	21,0	82	47,0	58

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	t <sub>3</sub> min	h	W			
GIR / GIR 35 UK-2RS	60	125	50	6	146,0	1,300

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952494081
Diámetro interior	35 mm
Diámetro interior	1.378" inch
Diámetro exterior	82 mm
Diámetro exterior	3.228" inch
Espesor	25 mm
Espesor	0.984" inch
Tipo	SI
Peso	1300 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE