

Rotulas SI

GIL40-UK-2RS-DURBAL - GIL40-UK-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/gil40-uk-2rs-durbal>

GIL40-UK-2RS



female thread: maintenance free, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE fabric

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: no lubrication necessary, maintenance free



order number	d	G	B	C ₁	C ₂	d ₂	d ₄
GIL 40 UK-2RS	40	M 39 x 3	28	23,0	92	52,0	65

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	t ₃ min	h	W			
GIR / GIL 40 UK-2RS	65	142	55	7	180,0	2,000

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952494128
Diámetro interior	40 mm
Diámetro interior	1.575" inch
Diámetro exterior	92 mm
Diámetro exterior	3.622" inch
Espesor	28 mm
Espesor	1.102" inch
Tipo	SI
Peso	2000 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE