

# Rotulas SI

## GIR70-UK-2RS-DURBAL - GIR70-UK-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/gir70-uk-2rs-durbal>

### GIR70-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.

rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	measurement [mm]	
GIR 70 UK-2RS	d	G
	B	C <sub>1</sub>
	d <sub>2</sub>	d <sub>3</sub>
	d <sub>4</sub>	h
	W	

  

type	measurement [mm]			load rating	weight
	t <sub>3 min</sub>	h	W	C <sub>0</sub> [kN]	[kg]
GIR / GIL 70 UK-2RS	80	200	85	610,0	8,600

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952494296
Diámetro interior	70 mm
Diámetro exterior	160 mm
Espesor	49 mm
Tipo	SI
Peso	8600 g
Hilo	Rosca derecha
Lubricación	sin
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE