

Rotulas SI

SIZJL15-DURBAL - SIJL15-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/sizjl15-durbal>

SIZJL15



female thread:
lubrication
required,
similar to
DIN ISO 12240-4,
series K,
measurement in
inches

Description: DIN ISO rod end K series. Dimensions
in inch. Sliding combination steel / steel.
Size ≥ 9 with grease nipple can be mounted upon
request.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
rod end body pressed around inner ring

Lubrication:
lubrication required



order number	d	B	C ₁	d ₂	G	d ₃	d ₄
SIZJL 15	15,88	19,05	12,29	38,10	5/8 - 18	21,84	25,40

type	inches	h ₁ min	W	h	α [°]	load rating C ₀ (kN)	weight (kg)
SIZJ / SIJL 15	5 / 8"	31,75	22,23	63,50	13,0	29,0	0,195

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952496917
Diámetro interior	15.88 mm
Diámetro exterior	38.1 mm
Espesor	19.05 mm
Tipo	SI
Peso	195 g
Hilo	Rosca izquierda
Lubricación	sin
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE