

Rotulas SI SI25-ES-DURBAL - SI25-ES-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/si25-es-durbal>

SI25-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	measurement (mm)						
d	G	B	C ₁	d ₂	d ₃	d ₄		
SI 25 ES		25	M 24 x 2	20	17,0	64	33,5	42

measurement [mm]

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SII 25 ES	48	36	94	7	83,0	0,64

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952497181
Diámetro interior	25 mm
Diámetro exterior	64 mm
Espesor	20 mm
Tipo	SI
Peso	640 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE