

## Rotulas SI

### SIL35-ES-2RS-DURBAL - SIL35-ES-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/sil35-es-2rs-durbal>

#### SIL35-ES-2RS



**female thread;**  
**lubrication**  
**required,**  
**according to**  
**DIN ISO 12240-4;**  
**series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

**Rod end body:**  
surface zinc plated

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIL 35 ES (-2RS)		35	M 36 x 3

type	measurement [mm]			$\alpha$ [°]	load rating $C_0$ [kN]	weight [kg]
	$l_1$ min	W	h			
SI / SIL 35 ES (-2RS)	60	50	125	6	146,0	1,3

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952497303
Diámetro interior	35 mm
Diámetro exterior	82 mm
Espesor	25 mm
Tipo	SI
Peso	1300 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE