

Rotulas SI SIL35-ES-DURBAL - SIL35-ES-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/sil35-es-durbal>

SIL35-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread
SIL 35 ES

| order number | | measurement [mm] | | | | | | |
|-------------------|------------------|------------------|----------|----|----------------|----------------|----------------|----------------|
| right hand thread | left hand thread | d | G | B | C ₁ | d ₂ | d ₃ | d ₄ |
| SIL 35 ES | | 35 | M 36 x 3 | 25 | 21,0 | 82 | 47,0 | 58 |

| type | measurement [mm] | | | α [°] | load rating C ₀ [kN] | weight [kg] |
|----------------|--------------------|----|-----|-----------------|---------------------------------------|----------------|
| | l ₃ min | W | h | | | |
| SI / SIL 35 ES | 60 | 50 | 125 | 6 | 146,0 | 1,3 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|-----------------|
| Marca | DURBAL |
| N° Ean13 | 3663952497310 |
| Diámetro interior | 35 mm |
| Diámetro interior | 1.378" inch |
| Diámetro exterior | 82 mm |
| Diámetro exterior | 3.228" inch |
| Espesor | 25 mm |
| Espesor | 0.984" inch |
| Tipo | SI |
| Peso | 1300 g |
| Hilo | Rosca izquierda |
| Lubricación | con |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE