

Rotulas SI

SI45-ES-2RS-DURBAL - SI45-ES-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/si45-es-2rs-durbal>

SI45-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGL...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number
right hand thread left hand thread

SI 45 ES (-2RS)	d	G	B	C ₁	d ₂	d ₃	d ₄
	45	M 42 x 3	32	27,0	102	58,0	70

measurement [mm]

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SII 45 ES (-2RS)	65	60	145	7	240,0	2,5

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952497518
Diámetro interior	45 mm
Diámetro exterior	102 mm
Espesor	32 mm
Tipo	SI
Peso	2500 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE