

## Rotulas SI SIL50-ES-DURBAL - SIL50-ES-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/sil50-es-durbal>

### SIL50-ES



**female thread; lubrication required, according to DIN ISO 12240-4; series E**

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2/R5 with additional seals also available.

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

**order number**

right hand thread	left hand thread	measurement [mm]					
		d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>4</sub>
SIL 50 ES		50	M 45 x 3	35	30,0	112	75

  

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	W	h			
SI / SIL 50 ES	68	65	160	6	290,0	3,5

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952497587
Diámetro interior	50 mm
Diámetro exterior	112 mm
Espesor	35 mm
Tipo	SI
Peso	3500 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE