

Rotulas SI SIL60-ES-DURBAL - SIL60-ES-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/sil60-es-durbal>

SIL60-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	measurement (mm)						
d	G	B	C ₁	d ₂	d ₃	d ₄		
SIL 60 ES		60	M 52 x 3	44	38,0	135	70,0	88

type	measurement [mm]				load rating C ₀ [kN]	weight [kg]
	l ₃ min	W	h	α [°]		
SI / SIL 60 ES	70	75	175	6	450,0	5,5

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952497631
Diámetro interior	60 mm
Diámetro exterior	135 mm
Espesor	44 mm
Tipo	SI
Peso	5500 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE