

Rotulas SI SI60-ES-2RS-DURBAL - SI60-ES-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/si/si60-es-2rs-durbal>

SI60-ES-2RS



female thread; lubrication required, according to DIN ISO 12240-4; series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

order number
right hand thread left hand thread

SI 60 ES (-2RS)

type	measurement [mm]				α [°]	load rating C_0 [kN]	weight [kg]
	l_2 min	W	h				
SI / SII 60 ES (-2RS)	70	75	175	6		450,0	5,5

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952497679
Diámetro interior	60 mm
Diámetro exterior	135 mm
Espesor	44 mm
Tipo	-
Peso	5500 g
Hilo	-
Lubricación	-
Envasado	-
Estándar	-

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE