

Rotulas SA SAL45-ES-2RS-DURBAL - SAL45-ES-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/sal45-es-2rs-durbal>

SAL45-ES-2RS



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Bad end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary

order number	measurement [mm]
right hand thread	d G B C1 d2
left hand thread	
SAL 45 ES (-2RS)	45 M 42 x 3 32 27,0 102

type	l1 min	l2	h	n [°]	load rating C0 [kN]	weight [kg]
SA / SAL 45 ES (-2RS)	94	51	163	7	240,0	2,600

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952498584
Diámetro interior	45 mm
Diámetro exterior	102 mm
Espesor	32 mm
Tipo	SA
Peso	2600 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE