

## Rotulas SA SAL60-ES-2RS-DURBAL - SAL60-ES-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/sal60-es-2rs-durbal>

### SAL60-ES-2RS



male thread:  
lubrication  
is necessary,  
according to  
DIN ISO 12240-4,  
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSA...ES-2RS with additional seals also available.


Ball end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and phosphated

Outer ring:  
bearing steel, hardened, ground and phosphated

Lubrication:  
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	
	SAL 60 ES (-2RS)	60	M 52 x 3	44	38,0	135	

type	measurement [mm]				n [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>	h				
SA / SAL 60 ES (-2RS)	115	60	210	6	450,0	5,900	

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952498744
Diámetro interior	60 mm
Diámetro exterior	135 mm
Espesor	44 mm
Tipo	SA
Peso	5900 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE