

Rotulas SA SAL70-ES-2RS-DURBAL - SAL70-ES-2RS-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/sal70-es-2rs-durbal>

SAL70-ES-2RS



male thread: lubrication is necessary, according to DIN ISO 12240-4, series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.

Bad end body: surface zinc plated

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication is necessary

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
	SAL 70 ES (-2RS)	70	M 56 x 4	49	42,0	160

type	measurement [mm]				n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h				
SA / SAL 70 ES (-2RS)	125	80	235	6	610,0	8,200	

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952498874
Diámetro interior	70 mm
Diámetro exterior	160 mm
Espesor	49 mm
Tipo	SA
Peso	8200 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE