

## Rotulas TAPR GIHO-K-12DO-DURBAL - DGIHO-K-12DO-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/tapr/dgiho-k-12do-durbal>

### GIHO-K-12DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555

**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple

order number		measurement [mm]								
right hand thread	left hand thread	d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>4</sub>	d <sub>5</sub>	B	C <sub>1</sub>	C <sub>2</sub>
GIHO-K 12 DO*		12	15,0	35	M 10 x 1,25	17	40	10	8	13

type	measurement [mm]				α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>			
GIHO-K / GIHO-KL 12 DO*	42	15	59,5	16	11	17,0	0,12

## CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952500607
Diámetro interior	12 mm
Diámetro exterior	35 mm
Espesor	8 mm
Tipo	TAPR
Peso	120 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE