

Rotulas TAPR GIHO-K-30DO-DURBAL - GIHO-K-30DO-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/tapr/giho-k-30do-durbal>

GIHO-K-30DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	B	C ₁	C ₂	
GIHO-K 30 DO		30	34,2	80	M 20 x 1,5	36	77	22	19	19

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 30 DO	85	29	125,0	35	6	108,0	1,25

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952500768
Diámetro interior	30 mm
Diámetro exterior	80 mm
Espesor	19 mm
Tipo	TAPR
Peso	1250 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE