

Rotulas TAPR GIHO-KL-40DO-DURBAL - GIHO-KL-40DO-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/tapr/giho-kl-40do-durbal>

GIHO-KL-40DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-KL 40 DO		
	d	d ₁ d ₂
	40	45,0 100
	M	27 x 2
	G	d ₄ d ₅ B C ₁ C ₂
	45	90 28 23 23

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 40 DO	105	37	155,0	45	7	156,0	2,16

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952500805
Diámetro interior	40 mm
Diámetro exterior	100 mm
Espesor	23 mm
Tipo	TAPR
Peso	2160 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE