

## Rotulas TAPR GIHO-K-60DO-DURBAL - GIHO-K-60DO-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/tapr/giho-k-60do-durbal>

**GIHO-K-60DO**

female thread:  
hydraulic rod ends,  
according to  
DIN 24555

**FERROBAL**

\* without grease nipple

**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Sliding combination:**  
steel / steel

**Inner ring:**  
bearing steel, hardened, ground and phosphated

**Outer ring:**  
bearing steel, hardened, ground and phosphated

**Lubrication:**  
lubrication required

order number		measurement [mm]									
right hand thread	left hand thread	d	d <sub>1</sub>	d <sub>2</sub>	G	d <sub>3</sub>	d <sub>4</sub>	B	C <sub>1</sub>	C <sub>2</sub>	
<b>GIHO-K 60 DO</b>		60	66,8	160	M 42 x 2	68	134	44	38	38	

type	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
<b>GIHN-K / GIHN-KL 60 DO</b>	150	57	230,0	68	6	380,0	7,15

### CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952500898
Diámetro interior	60 mm
Diámetro exterior	160 mm
Espesor	38 mm
Tipo	TAPR
Peso	7150 g
Hilo	Rosca derecha
Lubricación	con
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE