

Rotulas TPN GK80-DO-DURBAL - GK80-DO-DURBAL


<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/tpn/gk80-do-durbal>

GK80-DO



Description: DIN ISO Hydraulic rod end with welding slope and dowel pin at the end of rod. Made of spherical plain bearing DGE... ES (ES-2RS) pressed into rod end housing. Sliding combination steel / steel.
Type DGK...DO-2RS with two additional seals available on request with grease nipple.

hydraulic rod ends, according to DIN ISO 12240-4, series E



Sliding combination:

steel / steel

Inner ring:

bearing steel, hardened, ground and phosphated

Outer ring:

bearing steel, hardened, ground and phosphated

Lubrication:

lubrication required

* without grease nipple
** with grease nipple

order number	d	d ₁	d ₂	measurement [mm]			B	C ₁
GK 80 DO	80	89,4	180	6	95,0	55	47	

type	h ₁	l ₁	l ₂	measurement [mm]		D	d ₁	α [°]	load rating C ₀ [kN]	weight [kg]
GK 80 DO	141	231,0	98,0	5,0	120	105,0	6	6	620,0	8,700

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
N° Ean13	3663952501536
Diámetro interior	80 mm
Diámetro interior	3.15" inch
Diámetro exterior	180 mm
Diámetro exterior	7.087" inch
Espesor	55 mm
Espesor	2.165" inch
Tipo	TPN
Peso	8700 g
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE