

Rotulas SA

BRTM20-00-502-DURBAL - BRTM20-00-502-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/brtm20-00-502-durbal>

BRTM20-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₆	b ₁	b ₂	b ₃	
BRTM 20 -00	-502		20	M 20 x 1,5	24,5	50	25	18			
measurements [mm]		weight	rotational speed limit	basic load rating	dyn.	stat.					
type	h	l	b ₃	α [°]	[kg]	n _{max} [rpm]	C [N]	C ₀ [N]			
BRTM 20	78	47	28	7,0	0,340	825	17000	11700			

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952506777
Diámetro interior	20 mm
Diámetro exterior	50 mm
Espesor	25 mm
Tipo	SA
Peso	340 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE