

Rotulas SA

BRTM25-00-502-DURBAL - BRTM25-00-502-DURBAL

<https://www.123rodamiento.es/rodamiento-cojinete/rotulas/sa/brtm25-00-502-durbal>

BRTM25-00-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex-soap-grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₆	b ₁	b ₂	b ₃	
BRTM 25 -00	-502		25	M 24 x 2		29,5	64		31		22
measurements [mm]		weight		rotational speed limit		basic load rating		dyn.		stat.	
type	h	l	b ₃	α	[°]	[kg]	n _{max}	C	C ₁₀	C ₅₀	[N]
BRTM 25	94	57	30	5,0		0,596	600	24900			18500

CARACTERÍSTICAS DEL PRODUCTO

Marca	DURBAL
Nº Ean13	3663952506784
Diámetro interior	25 mm
Diámetro exterior	64 mm
Espesor	31 mm
Tipo	SA
Peso	596 g
Hilo	Rosca izquierda
Lubricación	con
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE